

IN THE CLAIMS:

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~striketrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please cancel claims 1-11 and add new claims 12-28 in accordance with the following:

1-11 canceled

12. (New) A method for determining a path to convey information from a first radio station to a second radio station via at least one intermediate radio station, the information being conveyed such that the first radio station and each intermediate radio station transfer the information to an adjacent radio station in a direction of the path, from a transferor radio station to a transferee radio station, comprising:

dividing a frequency band into a plurality of subbands for communication between the radio stations, with at least one subband being assigned to each radio station;

determining at least a portion of the path at a radio installation upon request of the first radio station;

transmitting path identification information from the radio installation to the first radio station;

transmitting from the radio installation to one or more intermediate radio station:

- the path identification information,
- Information identifying an other intermediate radio station and information identifying the subband assigned to it and/or identifying the first radio station and information identifying the subband assigned to it and/or identifying the second radio station and information identifying the subband assigned to it.

13. (New) The method according to claim 12, wherein,
in addition to the path identification information, the radio installation transmits to the first radio station:

information identifying the transferee radio station for the first radio station, and

information identifying the subband assigned to its transferee radio station, and the radio installation transmits to each intermediate radio station:

the path identification information,
information identifying the transferee radio station, and
information identifying the subband assigned to the transferee radio station.

14. (New) A method according to claim 13, wherein the radio installation transmits to each intermediate radio station:

- information identifying the transferor radio station for the intermediate radio station, and
- information identifying the subband assigned to the transferor radio station.

15. (New) A method according to claim 12, wherein, the radio installation transmits the path identification information to the second radio station.

16. (New) A method according to claim 15, wherein the radio installation also transmits to the second radio station:

- information identifying the transferor radio station for the second radio station and
- information identifying the subband assigned to the transferor radio station.

17. (New) A method according to claim 12, wherein, the radio stations of the radio communications system are combined into groups, each group has a single representative radio station, and the radio installation only communicates with the representative radio stations in transmitting the path identification information, the information identifying the radio station and the information identifying the subband assigned on it.

18. (New) A method according to claim 17, wherein in identifying the transferee radio station and the subband assigned to it:

the radio installation transmits information relating to the transferee radio station.

19. (New) A method according to claim 18, wherein in identifying the radio station and the subband assigned to it:

the radio installation also transmits information relating to the transferor radio station.

20. (New) A method according to claim 17, wherein,
at least one representative radio station forwards the path information and/or the information identifying the radio station and/or the information identifying the subband to at least one radio station of its group.

21. A method according to claim 12, wherein the radio installation informs at least one radio station of the subband assigned thereto when the radio installation transmits the path identification information.

22. (New) A method according to claim 17, wherein each representative radio station is in direct radio contact with all other radio stations of the group.

23. (New) The method according to claim 12, wherein the path identification information is a path number.

24. (New) A method according to claim 14, wherein,
the radio installation transmits the path identification information to the second radio station.

25. (New) A method according to claim 24, wherein the radio installation also transmits to the second radio station:

- information identifying the transferor radio station for the second radio station and
- information identifying the subband assigned to the transferor radio station.

26. (New) A method according to claim 19, wherein,
each representative radio station forwards the path information and/or sends information identifying the transferee radio station and/or sends information identifying the subband to at least one radio station of its group.

27. (New) A method according to claim 26, wherein the radio installation informs at least one radio station of the subband assigned thereto when the radio installation transmits the path identification information.

28. (New) A radio installation comprising:

a memory to store neighboring relationships between radio stations of a radio communications system;

means for assigning a subband to each radio station for communication with another radio station, each subband being part of a frequency band divided into a plurality of subbands;

a memory to store information about how the subbands have been assigned to the radio stations;

means for determining at least a portion of a path to convey information from a first radio station to a second radio station via at least one intermediate radio station, the information being conveyed such that the first radio station and each intermediate radio station transfer the information to an adjacent radio station in a direction of the path, from a transferor radio station to a transferee radio station, the path being determined upon receipt of a request;

a transmitter to transmit to an intermediate radio station:

- information identifying the path,
- Information identifying an other intermediate radio station and information

identifying the subband assigned to it and/or identifying the first radio station and information identifying the subband assigned to it and/or identifying the second radio station and information identifying the subband assigned to it.